

## AJ-HUBKIT-W

Ajax



## Features

---

AJAX professional anti-intrusion alarm system with bidirectional wireless communication.

Complete wireless alarm system for professional installations both in residential and commercial fields. The communication is done via Ethernet and/or GPRS. The two-way communication with detectors and accessories is accomplished using an Ajax-designed wireless protocol called Jeweller. This operates in the 868MHz frequency and it is secure enough to have earned the manufacturer a Grade 2 certification..

The wireless link has a high reliability due to its advanced Jeweller protocol with high security AES encryption. The unique instant and intelligent monitoring system detects inhibition of the signal identifying a specific downtime and in turn reduces maintenance costs as it significantly extends the life of the batteries of the detectors without compromising security. The wireless signal is able to cover distances up to 2 km in open space. It also includes features to ease the installation such as the Smart-Bracket or the simple linking of detectors to the alarm system.

It allows up to 100 wireless zones with the possibility of grouping these devices up to 9 different groups, where the different actions can be carried out; armed, partially armed, disarmed. These Ajax wireless devices have different possible configurations such as 24 hours zone, zone with time delay of entry or exit...

The AJ-HUB-W panel has an AC 110-250 V power input and also a rechargeable backup battery with a duration of up to 15 hours.

As an additional complement to the Ajax alarm system, from the mobile application you can add up to 10 IP cameras or video recorder channels to be able to verify the video stream live.

The kit includes the Ajax Hub AJ-HUB-W control panel, an AJ-DOORPROTECT-W magnetic contact, an AJ-MOTIONPROTECT-W motion detector and an AJ-SPACECONTROL-W remote control.

## Specifications

---

### Control Panel

Brand	AJAX
Security grade	Grade 2
RF frequency	868 MHz. Protocol via Jeweller wireless technology
Internal security	Tamper-resistant opening
Internal siren	Does not have
Communication	Ethernet / GPRS
Maximum devices	100 (max. 10 sirens)
Video integration	Up to 10 IP cameras or video recorder channels
Number of users	Up to 50
Connection with CRA	Contact ID / SIA
Housing material	ABS plastic
Power	AC 110~250 V, 50/60 Hz
Backup battery	Duration up to 15 hours
Temp. operation	+5° C ~ 40° C
Dimensions	163 (H) x 163 (W) x 36 (D) mm

### Magnetic Contact

Model	AJ-DOORPROTECT-W
Security grade	Grade 2
Transmission distance	? 2000 m (in open space)
Frequency	868 MHz
Battery	1 battery CR123A 3.0 V (approximate life time 7 years)
Housing material	ABS plastic
Dimensions	90 mm (D) x 20 (Ø) mm

## PIR detector

Model	AJ-MOTIONPROTECT-W
Technology	PIR Motion detector
Security grade	Grade 2
PIR lens	24 zones and 6 planes
Detection range	12 m / H: 88.5° / V: 80° / Installation 2.4 m
Pet immunity	? 20 kg, ? 50 cm
Frequency	868 MHz
Transmission distance	? 2000 m (in open space)
Anti-masking	Does not have
Sensitivity	Adjustable. 3 levels (low, medium and high)
LEDs indication	Alarm, tamper, signal
Battery	1 battery CR123A 3.0 V (approximate life time 7 years)
Temp. operation	0°C ~ 50°C
Housing material	ABS plastic
Dimensions (without bracket)	110 (H) x 65 (W) x 50 (D) mm

## Remote control

Model	AJ-SPACECONTROL-W
Power	1 battery CR2032 of 3 V
Transmission distance	? 1000 m (in open space)
Frequency	868 MHz
Battery	1 battery CR123A 3.0 V (approximate life time 5 years)
Temp. operation	-20° C ~ 50° C
Housing material	ABS plastic
Dimensions	65 (H) x 37 (W) x 10 (D) mm

# AJ-STARTERKIT-CAM-4G-W

Ajax



## Features

---

AJAX professional anti-intrusion alarm system with bidirectional wireless communication.

The wireless link has a high reliability due to its advanced Jeweller protocol with high security AES encryption. The unique instant and intelligent monitoring system detects inhibition of the signal identifying a specific downtime and in turn reduces maintenance costs as it significantly extends the life of the batteries of the detectors without compromising security. The wireless signal is able to cover distances up to 2 km in open space. It also includes features to ease the installation such as the Smart-Bracket or the simple linking of detectors to the alarm system.

It allows up to 100 wireless zones with the possibility of grouping these devices up to 9 different groups, where the different actions can be carried out; armed, partially armed, disarmed. These Ajax wireless devices have different possible configurations such as 24 hours zone, zone with time delay of entry or exit...

The panel AJ-HUB2-4G-W has an AC power input 110-250 V and also a rechargeable backup battery with duration of up to 16 hours. This central incorporates the Wings radio protocol to receive images from the AJ-MOTIONCAM-W photodetector.

Ethernet communication and 4G connection are its main advantage for remote access, both for the user and the installer, as it allows connection through the AJAX PRO Desktop PC software and the mobile applications for iOS and Android Ajax Security Systems (end user) and AJAX PRO: Tool for Engineers (professionals). Through these applications it is possible to configure the whole system, manage users and their permissions, add devices, group them in rooms and modify their settings. The use of the cloud is compatible with dynamic IP without opening ports.

The Ajax users will enjoy multiple advantages, as they can receive reliable and instant notifications in both desktop software and mobile applications. As an additional complement to the Ajax alarm system, from the mobile application you can add up to 25 IP cameras or video recorder channels to be able to verify the video stream live.

The kit includes the hub AJ-HUB2-4G-W, a photodetector AJ-MOTIONCAM-W, a magnetic contact AJ-DOORPROTECT-W and a remote control AJ-SPACECONTROL-W.

## Specifications

---

### Control Panel

Brand	Ajax
Security grade	Grade 2
Model	AJ-HUB2-4G-W
RF frequency	868 MHz. Protocol via Jeweller wireless technology
Internal security	Tamper-resistant opening
Internal siren	Does not have
Communication	Ethernet / Dual SIM 4G (LTE)
Maximum devices	100 (max. 10 sirens)
Video integration	Up to 25 IP cameras or video recorder channels
Number of users	Up to 50
Connection with CRA	Contact ID / SIA
Compatibility	Not compatible with ocBridge and uartBridge
Housing material	ABS plastic
Power	AC 110~250 V, 50/60 Hz
Backup battery	Duration up to 16 hours
Temp. operation	+5° C ~ 40° C
Dimensions	163 (H) x 163 (W) x 36 (D) mm

### PIRCAM

Model	AJ-MOTIONCAM-W
Technology	Volumetric PIR with photo camera
Security grade	Grade 2
PIR lens	24 zones and 6 planes
Detection range	12 m / H: 88.5° / V: 80° / Installation 2.4 m

<b>Frequency</b>	868 MHz Jeweller and Wings (sending images)
<b>Transmission distance</b>	? 1700 m in open space
<b>Pet immunity</b>	? 20 kg, ? 50 cm
<b>Anti-masking</b>	Does not have
<b>Sensitivity</b>	Adjustable. 3 levels (low, medium and high)
<b>Image resolution</b>	Up to VGA (640 x 480)
<b>Number of images</b>	Up to 5 images per detection
<b>Sending images</b>	Sending and receiving images in less than a minute
<b>Infrared lighting</b>	IR for night mode
<b>LEDs indication</b>	Alarm, tamper, signal
<b>Battery</b>	2 CR123A3.0 v-batteries (life up to 4 years)
<b>Compatibility</b>	AJ-HUB2-W/B
<b>Temp. operation</b>	0° C ~ 40° C
<b>Housing material</b>	ABS plastic
<b>Dimensions (without bracket)</b>	135 (H) x 70 (W) x 60 (D) mm

### **Magnetic contact**

<b>Model</b>	AJ-DOORPROTECT-W
<b>Security grade</b>	Grade 2
<b>Transmission distance</b>	? 2000 m in open space
<b>Frequency</b>	868 MHz
<b>Battery</b>	1 battery CR123A 3.0 V (approximate life time 7 years)
<b>Housing material</b>	ABS plastic
<b>Dimensions</b>	90 mm (D) x 20 (Ø) mm

### **Remote control**

<b>Model</b>	AJ-SPACECONTROL-W
--------------	-------------------

<b>Transmission distance</b>	? 1000 m in open space
<b>Frequency</b>	868 MHz
<b>Battery</b>	1 battery CR2032 3.0 V (approximate life time 5 years)
<b>Temp. operation</b>	-20 <sup>o</sup> C ~ 50 <sup>o</sup> C
<b>Housing material</b>	ABS plastic
<b>Dimensions</b>	65 (H) x 37 (W) x 10 (D) mm